

Package ‘eoffice’

June 20, 2019

Type Package

Title Export or Graph and Tables to 'Microsoft' Office and Import
Figures and Tables

Version 0.1.7

Author Kai Guo

Maintainer Kai Guo <guokai8@gmail.com>

Description Provides wrap functions to export and import graphics and data frames in R to 'microsoft' office. And This package also provide write out figures with lots of different formats. Since people may work on the platform without GUI support, the package also provide function to easily write out figures to lots of different type of formats. Now this package provide function to extract colors from all types of figures and pdf files.

License GPL-2

Imports officer, rvg, flextable, broom, dplyr, magrittr, tibble, ggplotify, R.devices, devEMF, magick, gplots, ggplot2, htmlwidgets, plotly

Depends

Encoding UTF-8

LazyData true

Suggests knitr, rmarkdown

VignetteBuilder knitr

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2019-06-20 14:50:09 UTC

R topics documented:

.gettext	2
.getfilename	2
.setcolnames	3
.theme_blank	3
convertplot	3
indocx	4
infigure	5
inoffice	6
inpptx	6
todoctx	7
toffice	8
tofigure	9
tohtml	9
topptx	10
totable	11

Index	12
--------------	-----------

.gettext	<i>get the suffix name</i>
----------	----------------------------

Description

get the suffix name

Usage

.gettext(x)

Arguments

x	filename
---	----------

.getfilename	<i>get the prefix name</i>
--------------	----------------------------

Description

get the prefix name

Usage

.getfilename(x)

Arguments

x	filename
---	----------

.setcolnames *set first row as column name*

Description

set first row as column name

Usage

.setcolnames(file)

Arguments

file input data frame

Author(s)

Kai Guo

.theme_blank *blank theme*

Description

blank theme

Usage

.theme_blank()

convertplot *convert basic plot to ggplot object*

Description

convert basic plot to ggplot object

Usage

convertplot(exp)

Arguments

exp expression formula of basic plot

Value

ggplot object

Author(s)

Kai Guo

Examples

```
p <- convertplot(plot(1:10))
class(p)
print(p)
```

indocx

read table from docx

Description

read table from docx

Usage

```
indocx(filename, header = FALSE)
```

Arguments

filename	input filename
header	use first row as column name

Author(s)

Kai Guo

Examples

```
totable(t.test(wt ~ am, mtcars), filename = file.path(tempdir(), "mtcars.docx"))
tabs <- indocx(filename = file.path(tempdir(), "mtcars.docx"), header = TRUE)
tabs
```

`infigure`*import figures and extract the colors used in the figures*

Description

import figures and extract the colors used in the figures

Usage

```
infigure(filename, format = NULL, exclude_col = NULL, topn = 10,  
  showfig = FALSE, showcol = FALSE, savegg = FALSE, density = 300,  
  pages = NULL)
```

Arguments

<code>filename</code>	input filename
<code>format</code>	format of input file
<code>exclude_col</code>	vector of colors to be excluded from the analysis
<code>topn</code>	display the most frequent colors
<code>showfig</code>	display the figure or not (default: FALSE)
<code>showcol</code>	display extracted colors or not (default: FALSE)
<code>savegg</code>	save the figure as ggplot2 object or not (default: FALSE)
<code>density</code>	resolution to render pdf
<code>pages</code>	integer vector with page numbers (pdf file). Defaults to all pages.

Author(s)

Kai Guo

Examples

```
if(interactive()){  
  require(ggplot2)  
  p <- ggplot(mtcars, aes(mpg, disp, color = factor(cyl))) + geom_point()  
  tofigure(p, filename = file.path(tempdir(), "mtcars.pdf"))  
  pp <- infigure(filename = file.path(tempdir(), "mtcars.pdf"), exclude_col="white")  
  pp  
}
```

inoffice *read tables from ppt and word*

Description

read tables from ppt and word

Usage

```
inoffice(filename, format = NULL, header = TRUE)
```

Arguments

filename	input filename
format	pptx or docx
header	use first row as column name

Author(s)

Kai Guo

Examples

```
## use tempdir for the example
totable(t.test(wt ~ am, mtcars), filename = file.path(tempdir(), "mtcars.docx"))
tabs <- inoffice(filename = file.path(tempdir(), "mtcars.docx"), header = TRUE)
tabs
```

inpptx *read table from pptx*

Description

read table from pptx

Usage

```
inpptx(filename, header = FALSE)
```

Arguments

filename	input filename
header	use first row as column name

Author(s)

Kai Guo

Examples

```
totable(t.test(wt ~ am, mtcars), filename = file.path(tempdir(), "mtcars.pptx"))
tabs <- inpptx(filename = file.path(tempdir(), "mtcars.pptx"), header = TRUE)
tabs
```

`todocx`*export figure to docx*

Description

export figure to docx

Usage

```
todocx(figure = NULL, filename = NULL, width = 6, height = 6,
       append = FALSE, devsize = FALSE, units = "in")
```

Arguments

<code>figure</code>	plot figure function
<code>filename</code>	output filename
<code>width</code>	width of the output figure
<code>height</code>	height of the output figure
<code>append</code>	append or not
<code>devsize</code>	Boolean value show use device size or not (default = FALSE)
<code>units</code>	the units in which to return the value – inches, cm, or pixels (device units)

Author(s)

Kai Guo

Examples

```
if(interactive()){
  plot(mtcars$mpg, mtcars$disp)
  todocx(filename = file.path(tempdir(), "mtcars.docx"))
  ## use ggplot2
  ggplot(mtcars, aes(mpg, disp, color = factor(cyl))) + geom_point()
  todocx(filename = file.path(tempdir(), "mtcars.docx"), height = 6, width = 4)
}
```

toffice *export graph to MS office*

Description

export graph to MS office

Usage

```
toffice(figure = NULL, format = "pptx", filename = "temp.pptx",  
       append = FALSE, width = 4, height = 4, devsize = FALSE,  
       units = "in")
```

Arguments

<i>figure</i>	plot figure function
<i>format</i>	file format
<i>filename</i>	output filename
<i>append</i>	append or not
<i>width</i>	width of the output figure
<i>height</i>	height of the output figure
<i>devsize</i>	Boolean value show use device size or not (default = FALSE)
<i>units</i>	the units in which to return the value – inches, cm, or pixels (device units)

Author(s)

Kai Guo

Examples

```
if(interactive()){  
  plot(mtcars$mpg, mtcars$disp)  
  toffice(filename = file.path(tempdir(), "mtcars.pptx"), format = "pptx")  
  ## use ggplot2  
  ggplot(mtcars, aes(mpg, disp, color = factor(cyl))) + geom_point()  
  toffice(filename = file.path(tempdir(), "mtcars.pptx"), format = "pptx")  
}
```

tofigure	<i>output figures to different formats</i>
----------	--

Description

output figures to different formats

Usage

```
tofigure(figure, format = NULL, filename = "temp.pdf")
```

Arguments

<i>figure</i>	output figure function, set NULL output the current figure
<i>format</i>	output format (could be ingored)
<i>filename</i>	output filename with different format as suffix

Author(s)

Kai Guo

Examples

```
require(ggplot2)
p <- ggplot(mtcars, aes(mpg, disp, color = factor(cyl))) + geom_point()
tofigure(p, filename = file.path(tempdir(), "mtcars.pdf"))
## or use ggplot directly
tofigure(ggplot(mtcars, aes(mpg, disp, color = factor(cyl))) +
geom_point(), filename = file.path(tempdir(), "mtcars.eps"))

## if you use basic plot function or other plot function you
## need first use convertplot to convert it to ggplot object
## when you are working on the platform without GUI
p <- convertplot(plot(1:10))
tofigure(p, filename = file.path(tempdir(), "mtcars.pdf"))
topptx(p, filename = file.path(tempdir(), "mtcars.pptx"))
```

tohtml	<i>export as plotly html (only support ggplot2 object)</i>
--------	--

Description

export as plotly html (only support ggplot2 object)

Usage

```
tohtml(figure, filename = "temp.html", save = TRUE)
```

Arguments

figure	output figure function, set NULL output the current figure
filename	output format (could be ingored)
save	save figure or not (default: TRUE)

Author(s)

Kai Guo

Examples

```
if(interactive()){
  require(ggplot2)
  p <- ggplot(mtcars, aes(mpg, disp, color = factor(cyl))) + geom_point()
  tohtml(p, filename = file.path(tempdir(), "mtcars.html"))
  ## or use ggplot directly
  ggplot(mtcars, aes(mpg, disp, color = factor(cyl))) +
  geom_point()
  tohtml(save = FALSE)
}
```

topptx

export figure to pptx

Description

export figure to pptx

Usage

```
topptx(figure = NULL, filename = NULL, width = 6, height = 6,
  append = FALSE, devsize = FALSE, units = "in")
```

Arguments

figure	plot figure function
filename	output filename
width	width of the output figure
height	height of the output figure
append	append or not
devsize	Boolean value show use device size or not (default = FALSE)
units	the units in which to return the value – inches, cm, or pixels (device units)

Author(s)

Kai Guo

Examples

```
if(interactive()){
  plot(mtcars$mpg, mtcars$disp)
  topptx(filename = file.path(tempdir(), "mtcars.pptx"))
  ## use ggplot2
  ggplot(mtcars, aes(mpg, disp, color = factor(cyl))) + geom_point()
  topptx(filename = file.path(tempdir(), "mtcars.pptx"))
}
```

totable	<i>write table out to pptx or docx</i>
---------	--

Description

write table out to pptx or docx

Usage

```
totable(data, filename, format = NULL, append = FALSE)
```

Arguments

data	datasets
filename	output filename
format	pptx or docx
append	append into file

Author(s)

Kai Guo

Examples

```
tt <- t.test(wt ~ am, mtcars)
totable(tt, filename = file.path(tempdir(), "mtcars.pptx"))
totable(t.test(wt ~ am, mtcars), filename = file.path(tempdir(), "mtcars.pptx"))
totable(head(mtcars), filename = file.path(tempdir(), "mtcars.docx"))
```

Index

`.gettext`, 2
`.getfilename`, 2
`.setcolnames`, 3
`.theme_blank`, 3

`convertplot`, 3

`indocx`, 4
`infigure`, 5
`inoffice`, 6
`inpptx`, 6

`todocx`, 7
`toffice`, 8
`tofigure`, 9
`tohtml`, 9
`topptx`, 10
`totable`, 11