

Package ‘export’

October 30, 2018

Type Package

Title Streamlined Export of Graphs and Data Tables

Version 0.2.2

Date 2018-09-18

Depends R (>= 3.0)

Imports stats, utils, datasets, grDevices, officer (>= 0.2.2), rvg (>= 0.1.8), xtable (>= 1.8-2), flextable (>= 0.4.3), rgl (>= 0.99.16), xml2 (>= 1.2.0), stargazer (>= 5.2.1), openxlsx (>= 4.0.17), broom (>= 0.4.4)

Suggests ggplot2 (>= 1.0)

Description Easily export 'R' graphs and statistical output to 'Microsoft Office' / 'LibreOffice', 'Latex' and 'HTML' Documents, using sensible defaults that result in publication-quality output with simple, straightforward commands. Output to 'Microsoft Office' is in editable 'DrawingML' vector format for graphs, and can use corporate template documents for styling. This enables the production of standardized reports and also allows for manual tidy-up of the layout of 'R' graphs in 'Powerpoint' before final publication. Export of graphs is flexible, and functions enable the currently showing R graph or the currently showing 'R' stats object to be exported, but also allow the graphical or tabular output to be passed as objects. The package relies on package 'officer' for export to 'Office' documents, and output files are also fully compatible with 'LibreOffice'. Base 'R', 'ggplot2' and 'lattice' plots are supported, as well as a wide variety of 'R' stats objects, via wrappers to xtable(), broom::tidy() and stargazer(), including aov(), lm(), glm(), lme(), glmnet() and coxph() as well as matrices and data frames and many more...

License GPL-2

BugReports <https://github.com/tomwenseleers/export/issues>

RoxygenNote 6.0.1

NeedsCompilation no

Author Tom Wenseleers [aut, cre],
Christophe Vanderaa [aut]

Maintainer Tom Wenseleers <tom.wenseleers@kuleuven.be>

Repository CRAN

Date/Publication 2018-10-30 16:30:15 UTC

R topics documented:

graph2bitmap	2
graph2office	4
graph2vector	7
rgl2bitmap	9
table2office	10
table2spreadsheet	15
table2tex	21

Index	25
--------------	-----------

graph2bitmap	<i>Save currently active R graph to bitmap format</i>
--------------	---

Description

Save the currently active R graph or a graph passed as an object or function to bitmap format with sensible defaults

Usage

```
graph2bitmap(x = NULL, file = "Rplot", fun = NULL, type = c("PNG",
  "JPG", "TIF"), aspectr = NULL, width = NULL, height = NULL, dpi = 300,
  scaling = 100, font = ifelse(Sys.info()["sysname"] == "Windows", "Arial",
  "Helvetica")[[1]], bg = "white", cairo = TRUE,
  tiffcompression = c("lzw", "rle", "jpeg", "zip", "lzw+p", "zip+p"),
  jpegquality = 99, ...)
```

```
graph2png(...)
```

```
graph2tif(...)
```

```
graph2jpg(...)
```

Arguments

x	given ggplot2 plot or lattice plot object to export; if set to NULL the currently active R graph will be exported; not supported for base R plots.
file	name of output file. Any extension is ignored and added according to the requested output type. If file already exists it is overwritten.
fun	plot passed on as a function used to create it; useful especially for base R plots.

type	desired output type - PNG, TIF or JPG are currently supported. PNG is the preferred format, as it is a lossless format, and compresses better than TIF.
aspectr	desired width to height aspect ratio. If set to NULL, the aspect ratio of the graphics device is used. Can also be combined with one value for either the desired width or height of the graph.
width	desired width in inches; can be combined with a desired aspect ratio aspectr.
height	desired height in inches; can be combined with a desired aspect ratio aspectr.
dpi	desired output in dpi; defaults to 600 dpi.
scaling	scale width & height by a certain percentage.
font	desired font to use for labels in PNG and TIFF output; defaults to "Arial" on Windows systems and to "Helvetica" on other systems.
bg	desired background colour, e.g. "white" or "transparent".
cairo	logical, specifying whether or not to use Cairographics for export.
tiffcompression	compression to use for TIF files.
jpegquality	quality of JPEG compression.
...	any other options are passed on to grDevices' png , tiff , or jpeg function (according to the supplied type).

Value

NULL

Functions

- `graph2png`: Save currently active R graph to png file
- `graph2tif`: Save currently active R graph to TIF file
- `graph2jpg`: Save currently active R graph to JPEG file

Author(s)

Tom Wenseleers

See Also

[graph2office](#), [graph2vector](#), [graph2svg](#), [graph2pdf](#), [graph2eps](#)

Examples

```
# Create a file name
filen <- tempfile(pattern = "ggplot") # or
# filen <- paste("YOUR_DIR/ggplot")

# Generate graphical output
library(ggplot2)
library(datasets)
```

```

x=qplot(Sepal.Length, Petal.Length, data = iris,
        color = Species, size = Petal.Width, alpha = I(0.7))
plot.fun <- function(){
  print(qplot(Sepal.Length, Petal.Length, data = iris,
             color = Species, size = Petal.Width, alpha = 0.7))
}

# There are 3 ways to use graph2bitmap():
### 1. Pass the plot as an object
graph2png(x=x, file=filen, dpi=400, height = 5, aspectr=4)
graph2tif(x=x, file=filen, dpi=400, height = 5, aspectr=4)
graph2jpg(x=x, file=filen, dpi=400, height = 5, aspectr=4)
### 2. Get the plot from current screen device
# Because the example uses screen devices
x
graph2png(file=filen, dpi=400, height = 5, aspectr=4)
graph2tif(file=filen, dpi=400, height = 5, aspectr=4)
graph2jpg(file=filen, dpi=400, height = 5, aspectr=4)

### 3. Pass the plot as a function
# Because the example uses screen devices
graph2png(file=filen, fun=plot.fun, dpi=400, height = 5, aspectr=4)
graph2tif(file=filen, fun=plot.fun, dpi=400, height = 5, aspectr=4)
graph2jpg(file=filen, fun=plot.fun, dpi=400, height = 5, aspectr=4)

```

graph2office

Save currently active R graph to Microsoft Office / LibreOffice format

Description

Save the currently active R graph or a graph passed as an object or function to Microsoft Office / LibreOffice format with sensible defaults

Usage

```

graph2office(x = NULL, file = "Rplot", fun = NULL, type = c("PPT",
  "DOC"), append = FALSE, aspectr = NULL, width = NULL, height = NULL,
  scaling = 100, paper = "auto", orient = ifelse(type[1] == "PPT",
  "landscape", "auto"), margins = c(top = 0.5, right = 0.5, bottom = 0.5, left
  = 0.5), center = TRUE, offx = 1, offy = 1, upscale = FALSE,
  vector.graphic = TRUE, ...)

```

```
graph2ppt(...)
```

```
graph2doc(...)
```

Arguments

x	given ggplot2 plot or lattice plot object to export; if set to NULL the currently active R graph will be exported; not supported for base R plots.
file	name of output file. Any extension is ignored and added according to the requested output type.
fun	plot passed on as a function used to create it; useful especially for base R plots.
type	desired output type - DOC for Word document, PPT for Powerpoint.
append	logical value - if TRUE and type=PPT it will append the graph to the given file, where file can also be a given corporate template. If append=FALSE any existing file will be overwritten. Currently ignored in Word export.
aspectr	desired width to height aspect ratio. If set to NULL, the aspect ratio of the active graphics device is used.
width	desired width in inches; can be combined with a desired aspect ratio aspectr.
height	desired height in inches; can be combined with a desired aspect ratio aspectr.
scaling	scale width & height by a certain percentage.
paper	desired paper size to use - "A5" to "A1" for Powerpoint export, or "A5" to "A3" for Word output; default "auto" automatically selects the paper size that fits your graph. Graphs that are too large to fit on a given paper size are scaled down.
orient	desired paper orientation - "auto", "portrait" or "landscape"; default to "auto" for Word output and to "landscape" for Powerpoint.
margins	vector with the desired margins that should be left blank in
center	logical specifying whether or not to center the graph in the exported Powerpoint.
offx	if center is set to FALSE, the desired x offset at which to place one's graph in Powerpoint output.
offy	if center is set to FALSE, the desired y offset at which to place one's graph in Powerpoint output.
upscale	logical specifying whether or not to upscale one's graph to make it page-filling (excluding the margins). Note that scaling may result in a different look of one's graph relative to how it looks on the screen due to the change in size.
vector.graphic	logical specifying whether or not to output in editable, vector DrawingML format. Defaults to TRUE, in which case editing the plot in Powerpoint or Word is then possible after first ungrouping the plot elements. If set to FALSE, the plot is rasterized to PNG bitmap format at a resolution of 300 dpi.
...	any other options are passed on to rvg's dml_pptx function.

Value

NULL

Functions

- graph2ppt: Save currently active R graph to a Microsoft Office PowerPoint/LibreOffice Impress presentation
- graph2doc: Save currently active R graph to a Microsoft Office Word/LibreOffice Writer document

Author(s)

Tom Wenseleers, Christophe Vanderaa

See Also

[graph2vector](#), [graph2svg](#), [graph2pdf](#), [graph2eps](#), [graph2bitmap](#), [graph2png](#), [graph2tif](#), [graph2jpg](#)

Examples

```
# Create a file name
filen <- tempfile(pattern = "ggplot") # or
# filen <- paste("YOUR_DIR/ggplot")

# Generate graphical output
library(ggplot2)
library(datasets)
x=qplot(Sepal.Length, Petal.Length, data = iris,
        color = Species, size = Petal.Width, alpha = I(0.7))
plot.fun = function(){
  print(qplot(Sepal.Length, Petal.Length, data = iris,
             color = Species, size = Petal.Width, alpha = I(0.7)))
}

# There are 3 ways to use graph2office():
### 1. Pass the plot as an object
graph2ppt(x=x, file=filen)
graph2doc(x=x, file=filen, aspectr=0.5)
### 2. Get the plot from current screen device
# Because the example uses screen devices
x
graph2ppt(file=filen, width=9, aspectr=2, append = TRUE)
graph2doc(file=filen, aspectr=1.7, append =TRUE)

### 3. Pass the plot as a function
# Because the example uses screen devices
graph2ppt(fun=plot.fun, file=filen, aspectr=0.5, append = TRUE)
graph2doc(fun=plot.fun, file=filen, aspectr=0.5, append = TRUE)

### Formatting options:
# Disable vectorized image export (export as a bitmap)
graph2ppt(x=x, file=filen, vector.graphic=FALSE, width=9,
         aspectr=sqrt(2), append = TRUE)
# Fill the slide with graph
graph2ppt(x=x, file=filen, margins=0, upscale=TRUE, append=TRUE)
# etc...
```

graph2vector

*Save currently active R graph to vector format***Description**

Save the currently active R graph or a graph passed as an object or function to vector format with sensible defaults

Usage

```
graph2vector(x = NULL, file = "Rplot", fun = NULL, type = "SVG",
  aspectr = NULL, width = NULL, height = NULL, scaling = 100,
  font = ifelse(Sys.info()["sysname"] == "Windows", "Arial",
    "Helvetica")[[1]], bg = "white", colormodel = "rgb", cairo = TRUE,
  fallback_resolution = 600, ...)
```

```
graph2svg(...)
```

```
graph2pdf(...)
```

```
graph2eps(...)
```

Arguments

x	given ggplot2 plot or lattice plot object to export; if set to NULL the currently active R graph will be exported; not supported for base R plots.
file	name of output file. Any extension is ignored and added according to the requested output type. If file already exists it is overwritten.
fun	plot passed on as a function used to create it; useful especially for base R plots.
type	desired output type - SVG, PDF or EPS are currently supported. SVG is the preferred format, and good for editing in Inkscape; PDF is good for printing; EPS is sometimes requested by journals, though lower quality, especially when semi-transparency is used, as this is rasterized to bitmap. graph2office is recommended for vector output to Microsoft Office.
aspectr	desired width to height aspect ratio. If set to NULL, the aspect ratio of the graphics device is used. Can also be combined with one value for either the desired width or height of the graph.
width	desired width in inches; can be combined with a desired aspect ratio aspectr.
height	desired height in inches; can be combined with a desired aspect ratio aspectr.
scaling	scale width & height by a certain percentage.
font	desired font to use for labels; defaults to "Arial" on Windows systems and to "Helvetica" on other systems. Fonts are embedded by default in EPS output.
bg	desired background colour, e.g. "white" or "transparent".

colormodel	desired colormodel in pdf or eps output when cairo=FALSE; currently allowed values are "rgb" (default), "cmyk", "srgb", "srgb+gray", "rgb-nogray", and "gray" (or "grey").
cairo	logical indicating whether or not to use the cairo graphics device for output to PDF or EPS, defaults to TRUE, thereby allowing for simulated semi-transparency in EPS output, by rasterizing semi-transparent sections, and automated font embedding.
fallback_resolution	resolution in dpi to use to rasterize non-supported vector graphics (e.g. semi-transparent vector elements in EPS) output).
...	any other options are passed on to svg , cairo_pdf , cairo_ps , pdf or postscript.

Functions

- `graph2svg`: Save currently active R graph to SVG format
- `graph2pdf`: Save currently active R graph to PDF format
- `graph2eps`: Save currently active R graph to EPS format

Author(s)

Tom Wenseleers

See Also

[graph2office](#), [graph2bitmap](#), [graph2png](#), [graph2tif](#), [graph2jpg](#)

Examples

```
# Create a file name
filen <- tempfile(pattern = "ggplot") # or
# filen <- paste("YOUR_DIR/ggplot")

# Generate graphical output
library(ggplot2)
library(datasets)
x=qplot(Sepal.Length, Petal.Length, data = iris,
        color = Species, size = Petal.Width, alpha = I(0.7))
plot.fun <- function(){
  print(qplot(Sepal.Length, Petal.Length, data = iris,
            color = Species, size = Petal.Width, alpha = 0.7))
}

# There are 3 ways to use graph2vector():
### 1. Pass the plot as an object
graph2svg(x=x, file=filen, aspectr=2, font = "Times New Roman",
         height = 5, bg = "white")
graph2pdf(x=x, file=filen, aspectr=2, font = "Arial",
         height = 5, bg = "transparent")
graph2eps(x=x, file=filen, aspectr=2, font = "Arial",
         height = 5, bg = "transparent")
```



```

### 2. Get the plot from current screen device
# Because the example uses screen devices
x
graph2svg(file=filen, aspectr=2, font = "Arial",
          height = 5, bg = "transparent")
graph2pdf(file=filen, aspectr=2, font = "Times New Roman",
          height = 5, bg = "white")
graph2eps(file=filen, aspectr=2, font = "Times New Roman",
          height = 5, bg = "white")

### 3. Pass the plot as a function
# Because the example uses screen devices
graph2svg(file=filen, fun = plot.fun, aspectr=2, font = "Arial",
          height = 5, bg = "transparent")
graph2pdf(file=filen, fun=plot.fun, aspectr=2, font = "Arial",
          height = 5, bg = "transparent")
graph2eps(file=filen, fun=plot.fun, aspectr=2, font = "Arial",
          height = 5, bg = "transparent")

```

rgl2bitmap

Save currently active rgl 3D graph to bitmap format

Description

Save currently active rgl 3D graph to bitmap format in current orientation

Usage

```

rgl2bitmap(file = "Rplot", type = c("PNG"))

rgl2png(...)

```

Arguments

file	name of output file. Any extension is ignored and added according to the requested output type. If file already exists it is overwritten.
type	desired output type - currently only PNG is supported.
...	passing the rgl2png arguments to rgl2bitmap

Value

NULL

Functions

- rgl2png: Save currently active rgl 3D graph to PNG format

Author(s)

Tom Wenseleers

Examples

```
# Create a file name
filen <- tempfile(pattern = "rgl") # or
# filen <- paste("YOUR_DIR/rgl")

# Generate a 3D plot using 'rgl'
x = y = seq(-10, 10, length = 20)
z = outer(x, y, function(x, y) x^2 + y^2)
rgl::persp3d(x, y, z, col = 'lightblue')

# Save the plot as a png
rgl2png(file = filen)
# Note that omitting 'file' will save in current directory
```

table2office	<i>Export statistical output to a table in Microsoft Office / LibreOffice format</i>
--------------	--

Description

Export currently showing R stats object or stats object obj to a Microsoft Office / LibreOffice table

Usage

```
table2office(x = NULL, file = "Rtable", type = c("PPT", "DOC"),
  append = FALSE, digits = 2, digitspvals = 2, trim.pval = TRUE,
  width = NULL, height = NULL, offx = 1, offy = 1,
  font = ifelse(Sys.info()["sysname"] == "Windows", "Arial",
  "Helvetica")[[1]], pointsize = 12, add.rownames = FALSE)
```

```
table2ppt(...)
```

```
table2doc(...)
```

Arguments

x	given R stats object to export; if set to NULL the output of the previous R command will be exported.
file	name of output file. The .pptx or .docx extension is added automatically.
type	desired output type - "PPT" for PowerPoint and "DOC" for Word.
append	logical value - if TRUE and type="PPT" or "DOC" it will append the table to the given file, where file can also be a given corporate. If append=FALSE any existing file will be overwritten.

<code>digits</code>	number of significant digits to show for all columns except for the column with p values.
<code>digitspvals</code>	number of significant digits to show for columns with p values.
<code>trim.pval</code>	a logical indicating if the p-values for which the significant digit is lower than the desired rounding digit (given by <code>digitspvals</code>) should be trimmed as <code>paste0("<", 10^-ndigitspvals)</code> (eg ' <code><0.01</code> ') otherwise they are rounded at <code>ndigitspvals</code> digits.
<code>width</code>	desired width of table in inches. If the given width exceeds the page or slide width, the table width becomes the page/slide width.
<code>height</code>	desired height of table in inches. If the given height exceeds the page or slide height, the table height becomes the page/slide height.
<code>offx</code>	x offset in inches to specify horizontal location of table (only for <code>type=="PPT"</code>).
<code>offy</code>	y offset in inches to specify vertical location of table (only for <code>type=="PPT"</code>).
<code>font</code>	desired font to use for output table; defaults to "Arial" on Windows systems and to "Helvetica" on other systems.
<code>pointsize</code>	desired font point size.
<code>add.rownames</code>	logical specifying whether or not to add row names.
<code>...</code>	Further arguments to be passed to <code>table2office</code> .

Details

Columns corresponding to degrees of freedom (with header "Df" or "df") are always given as integers. Objects that can be exported with `table2office` are all those supported by `xtable` and `tidy`. The function will first use `xtable` to format the data. If the data class is not supported by `xtable` the function will then use `tidy`. The data classes supported by `xtable` are:

- `anova`
- `aov`
- `aovlist`
- `data.frame`
- `glm`
- `gmsar`
- `lagImpact`
- `lm`
- `matrix`
- `prcomp`
- `sarlm`
- `sarlm.pred`
- `spautolm`
- `sphet`
- `splm`
- `stsls`

- `summary.aov`
- `summary.aovlist`
- `summary.glm`
- `summary.gmsar`
- `summary.lm`
- `summary.prcomp`
- `summary.sarlm`
- `summary.spautolm`
- `summary.sphet`
- `summary.splm`
- `summary.stsIs`
- `table`
- `ts`
- `zoo`

The data classes supported by `tidy` are:

- `aareg`
- `acf`
- `Arima`
- `betareg`
- `biglm`
- `binDesign`
- `binWidth`
- `brmsfit`
- `btergm`
- `cch`
- `character`
- `cld`
- `coefstest`
- `confint.glht`
- `cv.glmnet`
- `default`
- `density`
- `dgCMatrix`
- `dgTMatrix`
- `dist`
- `emmGrid`
- `ergm`

- felm
- fitdistr
- ftable
- gam
- Gam
- gamlss
- geeglm
- glht
- glmnet
- glmRob
- gmm
- htest
- ivreg
- kappa
- kde
- kmeans
- Line
- Lines
- list
- lme
- lmodel2
- lmRob
- logical
- lsmobj
- manova
- map
- Mclust
- merMod
- mle2
- muhaz
- multinom
- nlrq
- nls
- NULL
- numeric
- orcutt
- pairwise.htest

- plm
- poLCA
- Polygon
- Polygons
- power.htest
- pyears
- rcorr
- ref.grid
- ridgelm
- rjags
- roc
- rowwise_df
- rq
- rqs
- sparseMatrix
- SpatialLinesDataFrame
- SpatialPolygons
- SpatialPolygonsDataFrame
- spec
- speedlm
- stanfit
- stanreg
- summary.glm
- summaryDefault
- survdiff
- survexp
- survfit
- survreg
- tbl_df
- TukeyHSD

Value

`flextable` object

Functions

- `table2ppt`: Export statistical output to a table in a Microsoft Office PowerPoint/ LibreOffice Impress presentation
- `table2doc`: Export statistical output to a table in a Microsoft Office Word/ LibreOffice Writer document

Author(s)

Tom Wenseleers, Christophe Vanderaa

See Also

[table2tex](#), [table2html](#), [table2spreadsheet](#)

Examples

```
# Create a file name
filen <- tempfile(pattern = "table_aov") # or
# filen <- paste("YOUR_DIR/table_aov")

# Generate ANOVA output
fit=aov(yield ~ block + N * P + K, data = npk) # 'npk' dataset from base 'datasets'

# Save ANOVA table as a PPT
### Option 1: pass output as object
x=summary(fit)
table2ppt(x=x,file=filen, digits = 1, digitspvals = 3)
### Option 2: get output from console
summary(fit)
table2ppt(x=x,file=filen, width=5, font="Times New Roman", pointsize=14,
          digits=4, digitspvals=1, append=TRUE) # append table to previous slide

# Save ANOVA table as a DOC file
table2doc(x=x,file=filen, digits = 1, digitspvals = 3)
summary(fit)
table2doc(file=filen, width=3.5, font="Times New Roman", pointsize=14,
          digits=4, digitspvals=1, append=TRUE) # append table at end of document
```

table2spreadsheet	<i>Export statistical output to a table in spreadsheet compatible format (.xlsx or .csv)</i>
-------------------	--

Description

Export currently showing R stats object or stats object obj to a Microsoft Excel / LibreOffice Calc or comma-separated value file

Usage

```
table2spreadsheet(x = NULL, file = "Rtable", type = c("XLS", "CSV",
  "CSV2"), append = FALSE, sheetName = "new sheet", digits = 2,
  digitspvals = 2, trim.pval = TRUE, add.rownames = FALSE, ...)

table2excel(...)

table2csv(...)
```

```
table2csv2(...)
```

Arguments

x	given R stats object to export; if set to NULL the output of the previous R command will be exported.
file	name of output file. The .xlsx or .csv extension is added automatically.
type	desired output type - "XLS" for Excel and "CSV"/"CSV2" for CSV file. Note that type="CSV2" will generate a CSV file where the value separator is a semi-colon (";") and the decimal separator is a comma (",")
append	logical value - if TRUE and type="XLS" it will add a new worksheet to the given file, where file can also be a given corporate. append=FALSE any existing file will be overwritten.
sheetName	a string giving the name of the new sheet that is created (only for type=="XLS"). It must be unique (case insensitive) from any existing sheet name in the file.
digits	number of significant digits to show for all columns except for the column with p values.
digitspvals	number of significant digits to show for columns with p values.
trim.pval	a logical indicating if the p-values for which the significant digit is lower than the desired rounding digit (given by digitspvals) should be trimmed as $\text{paste0("<", 10^{-ndigitspvals})}$ (eg '<0.01') otherwise they are rounded at ndigitspvals digits.
add.rownames	logical specifying whether or not to add row names.
...	extra options are passed on to createStyle for the formatting of the worksheet. This is only applicable for type=="XLS".

Details

Columns corresponding to degrees of freedom (with header "Df" or "df") are always given as integers. Objects that can be exported with [table2office](#) are all those supported by [xtable](#) and [tidy](#). The function will first use [xtable](#) to format the data. If the data class is not supported by [xtable](#) the function will then use [tidy](#). The data classes supported by [xtable](#) are:

- anova
- aov
- aovlist
- data.frame
- glm
- gmsar
- lagImpact
- lm
- matrix
- prcomp

- sarlm
- sarlm.pred
- spautolm
- sphet
- splm
- stsls
- summary.aov
- summary.aovlist
- summary.glm
- summary.gmsar
- summary.lm
- summary.prcomp
- summary.sarlm
- summary.spautolm
- summary.sphet
- summary.splm
- summary.stsls
- table
- ts
- zoo

The data classes supported by [tidy](#) are:

- aareg
- acf
- Arima
- betareg
- biglm
- binDesign
- binWidth
- brmsfit
- btergm
- cch
- character
- cld
- coeftest
- confint.glm
- cv.glmnet
- default

- density
- dgCMatrix
- dgTMatrix
- dist
- emmGrid
- ergm
- felm
- fitdistr
- ftable
- gam
- Gam
- gamlss
- geeglm
- glht
- glmnet
- glmRob
- gmm
- htest
- ivreg
- kappa
- kde
- kmeans
- Line
- Lines
- list
- lme
- lmodel2
- lmRob
- logical
- lsmobj
- manova
- map
- Mclust
- merMod
- mle2
- muhaz
- multinom

- nlrq
- nls
- NULL
- numeric
- orcutt
- pairwise.htest
- plm
- poLCA
- Polygon
- Polygons
- power.htest
- pyears
- rcorr
- ref.grid
- ridgelm
- rjags
- roc
- rowwise_df
- rq
- rqs
- sparseMatrix
- SpatialLinesDataFrame
- SpatialPolygons
- SpatialPolygonsDataFrame
- spec
- speedlm
- stanfit
- stanreg
- summary.glht
- summaryDefault
- survdiff
- survexp
- survfit
- survreg
- tbl_df
- TukeyHSD

Value

A data frame

Functions

- `table2excel`: Export statistical output to a table in a Microsoft Office Excel/ LibreOffice Calc spreadsheet
- `table2csv`: Export statistical output to a table in a CSV format ("," for value separation and "." for decimal)
- `table2csv2`: Export statistical output to a table in a CSV format (";" for value separation and "," for decimal)

Author(s)

Tom Wenseleers, Christophe Vanderaa

See Also

[table2tex](#), [table2html](#), [table2office](#)

Examples

```
# Create a file name
filen <- tempfile(pattern = "table_aov") # or
# filen <- paste("YOUR_DIR/table_aov")

# Generate ANOVA output
fit=aov(yield ~ block + N * P + K, data = npk) # 'npk' dataset from base 'datasets'
x=summary(fit)

# Save ANOVA table as a CSV
### Option 1: pass output as object
table2csv(x=x,file=filen, digits = 1, digitspvals = 3)
### Option 2: get output from console
summary(fit)
table2csv(file=filen, digits = 2, digitspvals = 4)

# Save ANOVA table as an Excel
# Without formatting of the worksheet
x
table2excel(file=filen, sheetName="aov_noformatting",
            digits = 1, digitspvals = 3)
# With formatting of the worksheet
table2excel(x=x,file=filen, sheetName="aov_formated",
            append = TRUE, add.rownames=TRUE, fontName="Arial",
            fontSize = 14, fontColour = rgb(0.15,0.3,0.75),
            border=c("top", "bottom"), fgFill = rgb(0.9,0.9,0.9),
            halign = "center", valign = "center", textDecoration="italic")
```

table2tex	<i>Export statistical output to HTML or Latex table</i>
-----------	---

Description

Export currently showing R stats object or stats object obj to a HTML or Latex table

Usage

```
table2tex(x = NULL, file = "Rtable", type = "TEX", digits = 2,
  digitspvals = 2, trim.pval = TRUE, summary = FALSE, standAlone = TRUE,
  add.rownames = FALSE, ...)
```

```
table2html(...)
```

Arguments

x	given R stats object or list of stats objects to export; if set to NULL the output of the previous R command will be exported.
file	name of output file. The appropriate extension is added automatically.
type	desired output type - "TEX" for Latex and "HTML" for HTML.
digits	number of significant digits to show for all columns except for the column with p values.
digitspvals	number of significant digits to show for columns with p values.
trim.pval	a logical indicating if the p-values for which the significant digit is lower than the desired rounding digit (given by digitspvals) should be trimmed as <code>paste0("<", 10^-ndigitspvals)</code> (eg '<0.01') otherwise they are rounded at ndigitspvals digits.
summary	logical indicating whether or not to summarize data files.
standAlone	logical indicating whether exported Latex code should be standalone compilable, or whether it will be pasted into another document.
add.rownames	logical indicating whether the names of the rows should be added to the table (inserting a column before first column).
...	extra options are passed on to stargazer.

Details

Objects that can be exported are all those supported by [xtable](#), [tidy](#) (see [table2office](#) for an extensive list of supported methods), or [stargazer](#). The models supported by [stargazer](#) are:

- `aftreg (eha)`
- `anova (stats)`
- `aov (stats)`
- `aovlist (stats)`

- `arima` (stats)
- `betareg` (betareg)
- `binaryChoice` (sampleSelection)
- `bj` (rms)
- `brglm` (brglm)
- `censReg` (censReg)
- `coeftest` (lmtest)
- `coxph` (survival)
- `coxreg` (eha)
- `clm` (ordinal)
- `clogit` (survival)
- `cph` (rms)
- `dynlm` (dynlm)
- `ergm` (ergm)
- `errorsarlm` (spdev)
- `felm` (lfe)
- `gam` (mgcv)
- `garchFit` (fGarch)
- `gee` (gee)
- `glm` (stats)
- `Glm` (rms)
- `glmer` (lme4)
- `glmrob` (robustbase)
- `gls` (nlme)
- `Gls` (rms)
- `gmm` (gmm)
- `heckit` (sampleSelection)
- `hetglm` (glmx)
- `hurdle` (pscl)
- `ivreg` (AER)
- `lagarlm` (spdep)
- `lm` (stats)
- `lme` (nlme)
- `lmer` (lme4)
- `lmrob` (robustbase)
- `lrm` (rms)
- `maBina` (erer)

- `mclogit` (`mclogit`)
- `mlogit` (`mlogit`)
- `mnlogit` (`mnlogit`)
- `mlreg` (`eha`)
- `multinom` (`nnet`)
- `nlme` (`nlme`)
- `nlmer` (`lme4`)
- `ols` (`rms`)
- `pgmm` (`plm`)
- `phreg` (`eha`)
- `plm` (`plm`)
- `pmg` (`plm`)
- `polr` (`MASS`)
- `psm` (`rms`)
- `rem.dyad` (`relevent`)
- `rlm` (`MASS`)
- `rq` (`quantreg`)
- `Rq` (`rms`)
- `selection` (`sampleSelection`)
- `svyglm` (`survey`)
- `survreg` (`survival`)
- `tobit` (`AER`)
- `weibreg` (`eha`)
- `zeroin` (`pscl`)
- `relogit` (`zelig`)
- `cloglog.net` (`zelig`)
- `gamma.net` (`zelig`)
- `probit.net` (`zelig`)
- `logit.net` (`zelig`)

Value

NULL

Functions

- `table2html`: Export statistical output to HTML table

Author(s)

Tom Wenseleers, Christophe Vanderaa

See Also

[table2office](#), [table2ppt](#), [table2doc](#), [stargazer](#)

Examples

```
# Create a file name
filen <- tempfile(pattern = "table_aov") # or
# filen <- paste("YOUR_DIR/table_aov")

# Generate ANOVA output
fit=aov(yield ~ block + N * P + K, data = npk) # 'npk' dataset from base 'datasets'
x=summary(fit)

# Export to Latex in standAlone format
table2tex(x=x,file=filen)
# Export to Latex to paste in tex document
summary(fit) # get output from the console
table2tex(file=filen, standAlone = FALSE)

# Export to HTML
table2html(x=x,file=filen) # or
summary(fit) # get output from the console
table2html(file=filen)
```


Index

cairo_pdf, 8
cairo_ps, 8
createStyle, 16

dml_pptx, 5

flextable, 14

graph2bitmap, 2, 6, 8
graph2doc (graph2office), 4
graph2eps, 3, 6
graph2eps (graph2vector), 7
graph2jpg, 6, 8
graph2jpg (graph2bitmap), 2
graph2office, 3, 4, 7, 8
graph2pdf, 3, 6
graph2pdf (graph2vector), 7
graph2png, 6, 8
graph2png (graph2bitmap), 2
graph2ppt (graph2office), 4
graph2svg, 3, 6
graph2svg (graph2vector), 7
graph2tif, 6, 8
graph2tif (graph2bitmap), 2
graph2vector, 3, 6, 7

jpeg, 3

pdf, 8
png, 3

rgl2bitmap, 9
rgl2png (rgl2bitmap), 9

stargazer, 21, 24
svg, 8

table2csv (table2spreadsheet), 15
table2csv2 (table2spreadsheet), 15
table2doc, 24
table2doc (table2office), 10

table2excel (table2spreadsheet), 15
table2html, 15, 20
table2html (table2tex), 21
table2office, 10, 11, 16, 20, 21, 24
table2ppt, 24
table2ppt (table2office), 10
table2spreadsheet, 15, 15
table2tex, 15, 20, 21
tidy, 11, 12, 16, 17, 21
tiff, 3

xtable, 11, 16, 21